



2700 Series Flotation Bath

The temperature range of the water bath is room temperature to 100°C. With an accuracy of 0.5°C. This bath is suitable for the Washerman, Kolmer and Khan test in activations, Paraffin Embedding and many other applications in the laboratories.

The bath is constructed double walled inside, made of Stainless Steel and outside of Mild Steel Sheet duly painted epoxy power coating provided with 25 mm mineral wool insulation on five sides.

The temperature is controlled by a Hydraulic type thermostat room temperature to 80°C. With maximum temperature 100°C sensitivity of plus minus 0.5°C Heating elements are made of copper Nickle plated tubular type and approximately extend the full length of the bath. Control panel is provided at lower portion of the bath consisting of two neon pilot lights which indicates control cycles as well as the mains heater switch. temperature control knob- The bath is complete with perforated and removable diffuser shelves. Stainless Steel Cover, brass drain plug, Cord with Plug to work on 220/230 volts A.C. But without rack and thermometer.

Corporate & Regd. Office :

Analytical House, # E67 & E68, Ravi Park, Opp., Sainath Park, Vasna Road, Baroda, Gujarat - 390 015. INDIA

Tele : 0265-2253620 / 2252839 Fax : 0265-2254395

E-mail : info@hplctechnologies.com / info@ais-india.com Web : www.ais-india.com / www.analyticalgroup.net