



Volumetric Infusion Pump



ATL 5100 SERIES

Technical Specifications

1. Battery back-up operating time 5 hours.
2. LCD programming display
3. Data entry calculator style alpha numeric programming keyboard
4. Pole clamp Multi-function mounting clamp
5. Nurse call output alarm, time and date settings
6. Quick titration of rate or dose with volume-time programming
7. Flow rate range (primary) 0.1 to 99.9 ml/hr. (0.1 ml increments) and 1 to 1200 ml/hr. (1ml increments.)
8. Volume to be infused 0.1 to 99.9 ml (0.1ml increments) and 1 to 9999 ml(1 ml increments).
9. Both flow rates and volume to be infused be configured to limit the maximum allowable range



Corporate & Reg. Office: Analytical House, E67 & 68, Ravi Park, Opp. Sainath Park, Vasna Road, Baroda, Gujarat-390 015, INDIA. Tel.: 0091- 265-2253620, 2252839 Telefax: 0091-265-2254395
Email: info@ais-india.com, info@hplctechnologies.com, info@analyticalgroup.net
Web: www.ais-india.com / www.analyticalgroup.net / www.hplctechnologies.com

Note : Company reserves right to add/delete/modify the content / technical specification of the catalogue without prior notice. We are the only Tailor Making Company who provide Analytical Equipment based on Customer Requirement



10. RS232C/USB/RS485 output for Printer, PC connectivity and Data acquisition with selectable baud rate options be there.
11. Accuracy $\pm 3\%$.
12. Pump Database: events of 24 hours with real time.

System Configuration Accessories, spares and consumables

1. Compatible with any standard infusion sets available in local Indian market
2. 1000 numbers of required infusion sets be supplied with the single unit